



**ARDON**<sup>®</sup>  
**WORKWEAR**  
& **OUTDOOR**

# ARDON<sup>®</sup> DERRICK DENIM S1P


SAFETY SHOES



**DRY AIR**



**DEFUSE  
CONTROL**



**NONMETALLIC**



**FLAT ANTI-SLIP**

TECHNICAL SHEET



**ARDON**<sup>®</sup>  
**WORKWEAR**  
**& OUTDOOR**

# ARDON<sup>®</sup> DERRICK DENIM S1P

SAFETY SHOES

**ARTICLE** G3269

**MATERIAL**

Upper  
 Lining  
 Sole

ACTION NUBUK – cowhide leather with polyurethane / textile  
 MESH laminated breathable fabric  
 rubber, oil resistant, antistatic, anti-slip, glued technology

Toe cap  
 Plate  
 Insole

composite 459  
 kevlar

ANATOMIC FOAM anatomically shaped EVA foam, supports longitudinal and transverse arches, absorbs shocks in the heel area

**SIZE**

39-48

**UNIT**

pair

**PACKAGE**

Units in a carton

10 pairs

Units in a box

1 pair

**DIMENSIONS**

Carton H x W x D  
 (cm)

	39-42	43-48
Carton H x W x D (cm)	32.5 x 43.5 x 59.5	37.5 x 45.5 x 64.5

Carton (cbm)

	0,084	0,110
--	-------	-------

Size EUR

35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

Insole length mm

-	-	-	-	256	263	269	276	283	289	296	303	309	316	-	-	-
---	---	---	---	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	---	---	---

Foot length cm

-	-	-	-	25,1	25,8	26,4	27,1	27,8	28,4	29,1	29,8	30,4	31,1	-	-	-
---	---	---	---	------	------	------	------	------	------	------	------	------	------	---	---	---

**DESCRIPTION**

Safety shoe in modern street design. The upper of the shoe is made of durable fabric in a jeans look, the toe cap and heel are reinforced with action NUBUK material. The shoes are equipped with a composite toe and a flexible Kevlar insole against puncture. The stable flat sole made of rubber provides the highest level of anti-slip properties.

TECHNICAL SHEET



**ARDON**<sup>®</sup>  
**WORKWEAR**  
 & **OUTDOOR**

## NORMS

(EU) 2016/425

EN ISO 20345:2011 Personal protective equipment – Safety footwear

Category S1P SRC

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water		
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heat up to 300 °C		
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts	✓	
-		
-		
-		

TECHNICAL SHEET



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

<b>CODE</b>	<b>EAN</b>	<b>CARTON WEIGHT (KG)</b>	<b>UNIT WEIGHT (KG)</b>
G3269/39	8592390102768	13.64	1.364
G3269/40	8592390102775	13.94	1.394
G3269/41	8592390102782	14.43	1.443
G3269/42	8592390102799	14.50	1.450
G3269/43	8592390102805	15.51	1.551
G3269/44	8592390102812	15.95	1.595
G3269/45	8592390102829	16.57	1.657
G3269/46	8592390102836	17.25	1.725
G3269/47	8592390102843	17.72	1.772
G3269/48	8592390102850	17.91	1.791





**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**





**ARDON®**

**WORKWEAR  
& OUTDOOR**



TECHNICAL SHEET