



ARDON®
WORKWEAR
& OUTDOOR

ARDON® GRINDER S3

SAFETY SHOES



DRY AIR



**DEFUSE
CONTROL**



**WATER
REPELLENT**

TECHNICAL SHEET



ARDON[®]
WORKWEAR
 & **OUTDOOR**

ARDON[®] GRINDER S3

SAFETY SHOES

ARTICLE G3189

MATERIAL

Upper
 Lining
 Sole

Toe cap
 Plate
 Insole

ACTION NUBUK – cowhide leather with polyurethane / fabric coating
 MESH laminated breathable fabric
 PU/rubber, two-component spray coating, oil resistant, anti-static, antislip, resistant up to 300 °C
 composite 604
 kevlar
 ANATOMIC FOAM anatomically shaped EVA foam, supports longitudinal and transverse arches, absorbs shocks in the heel area

SIZE

UNIT

PACKAGE

Units in a carton
 Units in a box

36-48
 pair

10 pairs
 1 pair

DIMENSIONS

Carton H x W x D (cm)
 Carton (cbm)

	36-39	40-43	44-48
Carton H x W x D (cm)	31.5 x 45.5 x 61.5	33.5 x 47.5 x 61.5	37 x 49.5 x 64
Carton (cbm)	0,0881	0,0979	0,117

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	237	243	250	257	263	270	277	283	290	297	303	310	317	-	-	-
Foot length cm	-	22,7	23,3	24,0	24,7	25,3	26,0	26,7	27,3	28,0	28,7	29,3	30,0	30,7	-	-	-

DESCRIPTION

Safety ankle boot with upper made of ACTIONNUBUK material - cowhide leather with polyurethane coating. The wide PU / rubber sole has SRC anti-slip properties and is resistant to contact heat up to 300 ° C. The ANATOMIC FOAM insole ensures increased comfort of the shoes. The shoes are equipped with a composite toe and a flexible Kevlar insole against punctures.

TECHNICAL SHEET



ARDON[®]
WORKWEAR
 & **OUTDOOR**

NORMS

(EU) 2016/425

EN ISO 20345:2011 Personal protective equipment – Safety footwear

Category S3 HRO SRC

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water	✓	
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heatup to 300 °C	✓	
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts		
-		
-		
-		

TECHNICAL SHEET



ARDON®

**WORKWEAR
& OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3189/36	8592390074300	13.40	1.340
G3189/37	8592390074317	13.60	1.360
G3189/38	8592390074324	14.00	1.400
G3189/39	8592390074331	14.50	1.450
G3189/40	8592390074348	14.90	1.490
G3189/41	8592390074355	15.20	1.520
G3189/42	8592390074362	15.70	1.570
G3189/43	8592390074379	16.15	1.615
G3189/44	8592390074386	17.10	1.710
G3189/45	8592390074393	17.55	1.755
G3189/46	8592390074409	17.85	1.785
G3189/47	8592390074416	18.05	1.805
G3189/48	8592390074423	18.45	1.845





ARDON®
WORKWEAR
& OUTDOOR





ARDON®

**WORKWEAR
& OUTDOOR**



TECHNICAL SHEET