



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

## ARDON® PRIME HIGH S3

SAFETY SHOES



**DRY AIR**



**NONMETALLIC**



**WATER  
REPELLENT**

TECHNICAL SHEET



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

# ARDON® PRIME HIGH S3

SAFETY SHOES

**ARTICLE** G1300

**MATERIAL**

Upper cowhide leather with SPLIT LEATHER design, hydrophobic treatment  
 Lining MESH laminated breathable fabric  
 Sole PU/PU, two-component spray coating, oil resistant, anti-static, antislip  
 Toe cap composite Action 55  
 Plate kevlar  
 Insole FOAM COMFORT- anatomically shaped, absorbs shocks in the heel area

**SIZE** 36-48

**UNIT** pair

**PACKAGE**

Units in a carton 10 pairs  
 Units in a box 1 pair

**DIMENSIONS**

	36-41	42-44	45-48
Carton H x W x D (cm)	59,5 x 32,5 x 40	62 x 34 x 42	64,5 x 36 x 44
Carton (cbm)	0,0774	0,0089	0,1022

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	235	241	248	255	262	270	276	283	290	297	304	310	317	-	-	-
Foot length cm	-	22,5	23,1	23,8	24,5	25,2	26,0	26,6	27,3	28,0	28,7	29,4	30,0	30,7	-	-	-

**DESCRIPTION**

Safety ankle boots with hydrophobic treatment of the cowhide upper. The shoes are equipped with a composite toe cap and a flexible kevlar insole against punctures. It does not contain metal parts. The FOAM COMFORT insole takes care of the increased comfort of the shoes.

TECHNICAL SHEET



**ARDON**<sup>®</sup>  
**WORKWEAR**  
 & **OUTDOOR**

## NORMS

(EU) 2016/425

EN ISO 20345:2011 Personal protective equipment – Safety footwear

Category S3 SRA

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin		
WR - upper resistant to water	✓	
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS	✓	
HRO - resistance to contact heatup to 300 °C		
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts	✓	
-		
-		
-		

TECHNICAL SHEET



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

<b>CODE</b>	<b>EAN</b>	<b>CARTON WEIGHT (KG)</b>	<b>UNIT WEIGHT (KG)</b>
G1300/36	8592390072030	13.23	1.323
G1300/37	8592390072047	13.25	1.325
G1300/38	8592390072054	13.29	1.329
G1300/39	8592390072061	13.31	1.331
G1300/40	8592390072078	13.40	1.340
G1300/41	8592390072085	13.45	1.345
G1300/42	8592390072092	13.73	1.373
G1300/43	8592390072108	13.81	1.381
G1300/44	8592390072115	13.89	1.389
G1300/45	8592390072122	13.92	1.392
G1300/46	8592390072139	13.95	1.395
G1300/47	8592390072146	14.05	1.405
G1300/48	8592390072153	14.12	1.412





**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**





**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**



TECHNICAL SHEET