



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

## ARDON® PRIME LOW S1P

SAFETY SHOES



**DRY AIR**



**NONMETALLIC**

TECHNICAL SHEET



**ARDON**<sup>®</sup>  
**WORKWEAR**  
 & **OUTDOOR**

# ARDON<sup>®</sup> PRIME LOW S1P

SAFETY SHOES

**ARTICLE** G1301

**MATERIAL**

Upper cowhide leather with SPLIT LEATHER design  
 Lining MESH laminated breathable fabric  
 Sole PU/PU, two-component spray coating, oil resistant, anti-static, antislip  
 Toe cap composite Action 55  
 Plate kevlar  
 Insole FOAM COMFORT- anatomically shaped, absorbs shocks in the heel area

**SIZE** 36-48

**UNIT** pair

**PACKAGE**

Units in a carton 10 pairs  
 Units in a box 1 pair

**DIMENSIONS**

	36-41	42-44	45-48
Carton H x W x D (cm)	59,5 x 32,5 x 40	62 x 34 x 42	64,5 x 36 x 44
Carton (cbm)	0,0774	0,0089	0,1022

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	235	241	248	255	262	270	276	283	290	297	304	310	317	-	-	-
Foot length cm	-	23,0	23,6	24,3	25,0	25,7	26,5	27,1	28,3	28,5	29,2	29,9	30,5	31,2	-	-	-

**DESCRIPTION**

Safety low shoes with the cowhide upper. The shoes are equipped with a composite toe cap and a flexible kevlar insole against punctures. It does not contain metal parts. The FOAM COMFORT insole takes care of the increased comfort of the shoes.

TECHNICAL SHEET



**ARDON**<sup>®</sup>  
**WORKWEAR**  
 & **OUTDOOR**

## NORMS

(EU) 2016/425

EN ISO 20345:2011 Personal protective equipment – Safety footwear

Category S1P SRA

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin		
WR - upper resistant to water		
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS	✓	
HRO - resistance to contact heatup to 300 °C		
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts	✓	
-		
-		
-		

TECHNICAL SHEET



**ARDON**<sup>®</sup>  
**WORKWEAR**  
**& OUTDOOR**

<b>CODE</b>	<b>EAN</b>	<b>CARTON WEIGHT (KG)</b>	<b>UNIT WEIGHT (KG)</b>
G1301/36	8592390072160	12.85	1.285
G1301/37	8592390072177	12.87	1.287
G1301/38	8592390072184	12.89	1.289
G1301/39	8592390072191	12.91	1.291
G1301/40	8592390072207	12.96	1.296
G1301/41	8592390072214	13.10	1.310
G1301/42	8592390072221	13.25	1.325
G1301/43	8592390072238	13.36	1.336
G1301/44	8592390072245	13.40	1.340
G1301/45	8592390072252	13.41	1.341
G1301/46	8592390072269	13.46	1.346
G1301/47	8592390072276	13.49	1.349
G1301/48	8592390072283	13.51	1.351





**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**





**ARDON®**

**WORKWEAR  
& OUTDOOR**



TECHNICAL SHEET