

# TECHNICAL DATA SHEET

---

## PRIME SANTREK S1 SRA

### Safety shoes

Article NO: G1303

Upper: suede/ textile  
Sole: PU/ PU  
Description: trekking sandal with steel toe cap



Size: 36 - 48

---

Trekking sandal with steel toecap, antistatic sole with pattern - oil resistance and resistance of contact heat to 110°C. Colour gray-blue.

---

### Type and degree of protection:

Category	EN ISO 20345
Antistatic properties	X
Absorption of energy in the heel area	X
Sole with pattern- oil resistance	X
Safety toecap for toe protection	X
Slip resistant ceramic tile floor with SLS (SRA)	X



---

This personal protective equipment is in conformity with this harmonized European Standard:

EN ISO 20345:2011 : Personal protective equipment - safety shoes.  
Slip resistance on ceramic tile floor with SLS (SRA mark).

Certified by notified body no. 2369 (VIPO), dated 30<sup>th</sup> September 2016,  
Certificate number 00081/111/1/2016.

---

Pairs in carton: 10  
Carton weight: 15,7 kg  
Carton size: 0,089 m<sup>3</sup>

---



The shoes have to be perfect as for form and size, because they have rigid parts. The right size has to be found by measuring practically and carefully the shoes. The closing system has to be used correctly. The laces have to be tightened well without leaving too long free tops. The shoes have to be cleaned and treated with right, specific products, following the instructions for use. Do not keep footwear near heatings when not used and let them dry in a windy or room temperature. Before wearing and when cleaned, the shoes have to be controlled in order to find out visible defects existing, like closing system function, outsole profile's water, possible damages, etc. To define the right type of footwear to wear in every environment, the possible dangers and the place/ environment have to be included (e.g. construction industry, high temperatures, etc.). The shoes have to be stored correctly, keeping them in the proper packing.

---