



ARDON®
WORKWEAR
& OUTDOOR

ARDON® ROVER LOW S3 HRO

SAFETY SHOES



DRY AIR



FOOT COMFORT



WATER
REPELLENT

TECHNICAL SHEET



ARDON[®]
WORKWEAR
 & **OUTDOOR**

ARDON[®] ROVER S3 HRO

SAFETY SHOES

ARTICLE G3308

MATERIAL

Upper ACTION NUBUK- cowhide leather with polyurethane coating, hydrophobic MESH
 Lining laminated breathable fabric
 Sole PU/rubber, two-component spray coating, oil resistant, anti-static, antislip, resistant up to 300 ° C
 Toe cap composite 431
 Plate kevlar
 Insole ANATOMIC FOAM – anatomically shaped EVA foam, supports longitudinal and transverse arches, absorbs shocks in the heel area

SIZE
UNIT

35-50
 pair

PACKAGE

Units in a carton
 Units in a box

10 pairs
 1 pair

DIMENSIONS

Carton H x W x D (cm)
 Carton (cbm)

	35-42	43-48	49-50
Carton H x W x D (cm)	64,5x 34 x 43,5	67x 38 x 47,5	69,5x41x57,5
Carton (cbm)	0,0954	0,1209	0,1638

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	232	239	246	253	259	266	273	280	287	293	300	306	313	319	325	332	-
Foot length cm	22,7	23,5	24,1	24,8	25,4	26,1	26,8	27,5	28,2	28,7	29,5	30,1	30,8	31,4	32,0	32,7	-

DESCRIPTION

Safety shoes with an extra wide sole, resistant to contact heat up to 300 ° C and with an upper made of leather with a PU coating. The ANATOMIC FOAM insole ensures increased comfort of the shoes. The shoes are equipped with a composite toe cap and a kevlar insole against punctures.

TECHNICAL SHEET



ARDON[®]
WORKWEAR
& OUTDOOR

NORMS

(EU) 2016/425

EN ISO 20345:2011

Personal protective equipment - Safety footwear

Category

S3 HRO SRC CI HI

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WRU - upper resistant to water	✓	
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heat up to 300 °C	✓	
HI-insulation of the bottom of the shoe against heat	✓	
CI-insulation of the bottom of the shoe against the cold	✓	
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts		
-		
-		
-		

TECHNICAL SHEET



ARDON®

**WORKWEAR
& OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3308/35	8592390133403	17.3	1.73
G3308/36	8592390141972	17.4	1.74
G3308/37	8592390107824	17.5	1.75
G3308/38	8592390107831	17.6	1.76
G3308/39	8592390107848	17.6	1.76
G3308/40	8592390107855	17.7	1.77
G3308/41	8592390107862	17.8	1.78
G3308/42	8592390107879	18.0	1.80
G3308/43	8592390107886	18.2	1.82
G3308/44	8592390107893	18.5	1.85
G3308/45	8592390107909	18.7	1.87
G3308/46	8592390107916	18.9	1.89
G3308/47	8592390107923	19.0	1.90
G3308/48	8592390107930	19.2	1.92
G3308/49	8592390133410	19.4	1.94
G3308/50	8592390133427	19.6	1.96





ARDON®
WORKWEAR
& OUTDOOR





ARDON®

**WORKWEAR
& OUTDOOR**



TECHNICAL SHEET