

# TECHNICAL DATA SHEET

## FLYKER S1P SRC

### Safety shoes

Article no: G3324 (blue)  
G3325 (grey)

Upper : knitwear  
Sole: phylon/rubber

Size: 36 - 47



Fly-knit low shoes with composite toecap and kevlar midsole.

### Type and degree of protection:

Category	EN ISO 20345
Antistatic properties	x
Absorption of energy in the heel area	x
Sole with pattern- oil resistance	x
Puncture resistance (kevlar insole)	x
Composite toecap for toe protection	x
Slip resistant ceramic tile floor with SLS and on steel floor with glycerol (SRC)	x



This personal protective equipment is in conformity with this harmonized European Standard:

EN 20345:2011 - Personal protective equipment - safety shoes.

Slip resistance on ceramic tile floor with SLS and on steel floor with glycerol (SRC mark).

Certified by notified body no. 0075 (CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France), certificate number 0075/2737/161/11/20/2733.

Pairs in carton: 10  
Carton weight: 13,6 kg  
Carton size: 0,075 m<sup>3</sup>

The shoes have to be perfect as for from and size, because they have rigid parts. The right size has to be found by measuring practically and carefully the shoes. The closing system has to be used correctly. The laces have to be tightened well without leaving too long free tops. The shoes have to be cleaned and treated with right, specific products, following the instructions for use. Do not keep footwear near heatings when not used and let them dry in a windy or room temperature. Before



wearing and when cleaned, the shoes have to be controlled in order to find out visible defects existing, like closing system function, outsole profile's water, possible damages, etc. To define the right type of footwear to wear in every environment, the possible dangers and the place/ environment have to be included (e.g. construction industry, high temperatures, etc.). The shoes have to be stored correctly, keeping them in the proper packing.

---