



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

# ARDON® FORELOW S1P

SAFETY SHOES



DRY AIR



DEFUSE  
CONTROL

TECHNICAL SHEET



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

# ARDON® FORELOW S1P

SAFETY SHOES

**ARTICLE** G3197

**MATERIAL**

Upper  
 Lining  
 Sole

ACTION NUBUK – cowhide leather with polyurethane / fabric coating  
 MESH laminated breathable fabric  
 PU/rubber, two-component spray coating, oil resistant, anti-static,  
 antislip, resistant up to 300 °C

Toe cap  
 Plate  
 Insole

composite 604  
 kevlar

ANATOMIC FOAM anatomically shaped EVA foam, supports  
 longitudinal and transverse arches, absorbs shocks in the heel area

**SIZE**

**UNIT**

**PACKAGE**

Units in a carton  
 Units in a box

36-48

pair

10 pairs

1 pair

**DIMENSIONS**

Carton H x W x D  
 (cm)

36-39	40-43	44-48
31.5 x 41.5 x 61.5	33.5 x 43.5 x 61.5	37 x 43.5 x 64

Carton (cbm)

0,0804	0,0896	0,103
--------	--------	-------

Size EUR

35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

Insole length mm

-	237	243	250	257	263	270	277	283	290	297	303	310	317	-	-	-
---	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	---	---	---

Foot length cm

-	23,2	23,8	24,5	25,2	25,8	26,5	27,2	27,8	28,5	29,2	29,8	30,5	31,2	-	-	-
---	------	------	------	------	------	------	------	------	------	------	------	------	------	---	---	---

**DESCRIPTION**

Safety low shoes with upper made of ACTIONNUBUK material - cowhide leather with polyurethane coating. The wide PU / rubber sole has SRC anti-slip properties and is resistant to contact heat up to 300 ° C. The ANATOMIC FOAM insole ensures increased comfort of the shoes. The shoes are equipped with a composite toe and a flexible Kevlar insole against punctures.

TECHNICAL SHEET



**ARDON**<sup>®</sup>  
**WORKWEAR**  
 & **OUTDOOR**

## NORMS

(EU) 2016/425

EN ISO 20345:2011 Personal protective equipment – Safety footwear

Category S1P HRO SRC

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water		
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heatup to 300 °C	✓	
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts		
-		
-		
-		

TECHNICAL SHEET





**ARDON®**

**WORKWEAR  
& OUTDOOR**

<b>CODE</b>	<b>EAN</b>	<b>CARTON WEIGHT (KG)</b>	<b>UNIT WEIGHT (KG)</b>
G3197/36	8592390074782	13.10	1.310
G3197/37	8592390074799	13.50	1.350
G3197/38	8592390074805	13.80	1.380
G3197/39	8592390074812	14.20	1.420
G3197/40	8592390074829	14.80	1.480
G3197/41	8592390074836	15.60	1.560
G3197/42	8592390074843	15.80	1.580
G3197/43	8592390074850	16.40	1.640
G3197/44	8592390074867	16.70	1.670
G3197/45	8592390074874	17.20	1.720
G3197/46	8592390074881	17.80	1.780
G3197/47	8592390074898	18.40	1.840
G3197/48	8592390074904	19.10	1.910







**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**





**ARDON®**

**WORKWEAR  
& OUTDOOR**



TECHNICAL SHEET