



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

# ARDON® TURNER S1P

SAFETY SHOES



**DRY AIR**



**DEFUSE CONTROL**



**REFLECTIVE**

TECHNICAL SHEET



**ARDON**<sup>®</sup>  
**WORKWEAR**  
**& OUTDOOR**

# ARDON<sup>®</sup> TURNER S1P

SAFETY SHOES

**ARTICLE** G3282

**MATERIAL**

Upper brushed cowhide VELOR / fabric  
 Lining MESH laminated breathable fabric  
 Sole PU/rubber, two-component spray coating, oil resistant, anti-static, antislip, resistant up to 300 °C  
 Toe cap steel 604  
 Plate steel  
 Insole ANATOMIC FOAM anatomically shaped EVA foam, supports longitudinal and transverse arches, absorbs shocks in the heel area

**SIZE**

**UNIT**

**PACKAGE**

Units in a carton 10 pairs  
 Units in a box 1 pair

**DIMENSIONS**

	36-39	40-43	44-48
Carton H x W x D (cm)	31.5 x 41.5 x 61.5	33.5 x 43.5 x 61.5	37 x 43.5 x 64
Carton (cbm)	0,0804	0,0896	0,103

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	237	243	250	257	263	270	277	283	290	297	303	310	317	-	-	-
Foot length cm	-	23,2	23,8	24,5	25,2	25,8	26,5	27,2	27,8	28,5	29,2	29,8	30,5	31,2	-	-	-

**DESCRIPTION**

Low shoes in elegant trendy design. Upper is made of brushed cowhide VELUR and fabric, reinforced in the toe, heel and ankle. The wide PU / rubber sole has SRC anti-slip properties and is resistant to contact heat up to 300 ° C. The ANATOMIC FOAM insole ensures increased comfort of the shoes. For higher visibility, the shoe has a reflective strip in the heel. The shoes have a steel toe cap and an anti-puncture insole.

TECHNICAL SHEET



**ARDON**<sup>®</sup>  
**WORKWEAR**  
 & **OUTDOOR**

## NORMS

(EU) 2016/425

EN ISO 20345:2011 Personal protective equipment – Safety footwear

Category S1P SRC

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water		
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heat up to 300 °C		
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts		
-		
-		
-		

TECHNICAL SHEET



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

<b>CODE</b>	<b>EAN</b>	<b>CARTON WEIGHT (KG)</b>	<b>UNIT WEIGHT (KG)</b>
G3282/36	8592390102997	13.95	1.395
G3282/37	8592390103000	14.30	1.430
G3282/38	8592390103017	14.45	1.445
G3282/39	8592390103024	15.00	1.500
G3282/40	8592390103031	15.75	1.575
G3282/41	8592390103048	15.95	1.595
G3282/42	8592390103055	16.20	1.620
G3282/43	8592390103062	17.00	1.700
G3282/44	8592390103079	17.55	1.755
G3282/45	8592390103086	18.00	1.800
G3282/46	8592390103093	18.30	1.830
G3282/47	8592390103109	18.70	1.870
G3282/48	8592390103116	19.10	1.910





**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**





**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**



TECHNICAL SHEET