




ARDON[®]
WORKWEAR
& OUTDOOR

ARDON[®] TIMON S1P ESD

SAFETY SHOES



DRY AIR



NONMETALLIC



ESD

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

ARDON® TIMON S1P ESD

SAFETY SHOES

ARTICLE G3386

MATERIAL

Upper VELUR brushed cowhide leather / OXFORD fabric
 Lining MESH laminated breathable fabric
 Sole PU/PU, two-component spray coating, oil resistant, anti-static, antislip
 Toe cap Fibreglass 189
 Plate Kevlar
 Insole FOAM COMFORT – anatomically shaped, shock-absorbing in the heel area

SIZE 36-48

UNIT pair

PACKAGE

Units in a carton 10 pairs
 Units in a box 1 pair

DIMENSIONS

	36-39	40-42	43-48	-
Carton H x W x D (cm)	61 x 32 x 38	63,5 x 34 x 40,5	62 x 36,5 x 42	-
Carton (cbm)	0,0741	0,0874	0,0950	-

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	241	247	253	260	267	274	280	286	293	300	307	314	320	-	-	-
Foot length cm	-	23,6	24,2	24,8	25,5	26,2	26,9	27,5	28,1	28,8	29,5	30,2	30,9	31,5	-	-	-

DESCRIPTION

Safety low shoes with uppers made of VELUR brushed cowhide leather and OXFORD fabric. The FOAM COMFORT removable insole provides increased foot comfort. The lightweight dual-density polyurethane outsole meets SRC slip resistance requirements. The shoes do not have any metal parts; safety at work is ensured through the fibreglass toecap and flexible Kevlar insole in the sole. The model is ESD, i.e. it protects against electrostatic discharge and can be used on EPA premises.

TECHNICAL SHEET



ARDON[®]
WORKWEAR
 & **OUTDOOR**

NORMS

(EU) 2016/425

EN ISO 20345:2011

EN 61340-5-1:2016

Personal protective equipment - Safety footwear
 Protection of electronic devices from electrostatic
 phenomena - General requirements

Category S1P SRC ESD

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water		
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heat up to 300 °C		
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises	✓	
The shoes do not contain metal parts	✓	
-		
-		
-		

TECHNICAL SHEET



ARDON®

**WORKWEAR
& OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3386/36	8592390153906	13.61	1.361
G3386/37	8592390153913	13.86	1.386
G3386/38	8592390153920	14.11	1.411
G3386/39	8592390153937	14.36	1.436
G3386/40	8592390153944	14.61	1.461
G3386/41	8592390153951	14.86	1.486
G3386/42	8592390153968	15.11	1.511
G3386/43	8592390153975	15.36	1.536
G3386/44	8592390153982	15.61	1.561
G3386/45	8592390153999	15.86	1.586
G3386/46	8592390154002	16.11	1.611
G3386/47	8592390154019	16.36	1.636





ARDON®
WORKWEAR
& OUTDOOR





ARDON®

**WORKWEAR
& OUTDOOR**



TECHNICAL SHEET