

TECHNICAL DATA SHEET

FIRSAN S1P SRA

Safety shoes

Article NO: G1188

Upper: cow leather Liner: non-woven fabric, foam Sole: PU2D Description: full-leather sandal textil tightening steel toecap, midplate

Size: 35 - 50

PU2D sole is antiwriting, resistant to oils and fuels and contact heat up to 110°C. It is antistatic and absorbes shocks up to 20 J in the heel area. Design of the sole provides high adhesion to the surface and the profile significantly reduce the risk of slip. This shoes are suitable for use at construction industry.

Type and degree of protection:

Kategorie	EN ISO 20345
Antistatic properties	x
Absorption of energy in the heel area	x
Sole with pattern- oil resistance	x
Safety toecap for toe protection	x
Puncture resistance (protective insole)	х
Slip resistance on ceramic tile floor with SLS (SRA mark)	x



This personal protective equipment is in conformity with this harmonized European Standard:

EN ISO 20344:2011 : Personal protective equipment - Test methods for footwear. EN ISO 20345:2011 : Personal protective equipment - Safety shoes. Slip resistance on ceramic tile floor with SLS (SRA mark). Certified by notified body no. 2369 (VIPO), Certificate number 00064/111/1/2019.



Pairs in carton:	10
Carton weight:	15,7 kg
Carton size:	0,089 m³
Country of origin:	China

The shoes have to be perfect as for from and size, because they have rigid parts. The right size has to be found by measuring practically and carefully the shoes. The closing system has to be used correctly. The laces have to be tightened well without leaving too long free tops. The shoes have to be cleaned and treated with right, specific products, following the instructions for use. Do not keep footwear near heatings when not used and let them dry in a windy or room temperature. Before wearing and when cleaned, the shoes have to be controlled in order to find out visible defects existing, like closing system function, outsole profile's water, possible damages, etc. To define the right type of footwear to wear in every environment, the possible dangers and the place/ environment have to be indeded (e.g. construction industry, high temperatures, etc.). The shoes have to be stored correctly, keeping them in the proper packing.