



ARDON®
WORKWEAR
& OUTDOOR

ARDON® VISPERSAN GREY S1P

SAFETY SHOES



DRY AIR



DEFUSE CONTROL



NONMETALLIC



REFLECTIVE

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

ARDON® VISPERSAN GREY S1P

SAFETY SHOES

ARTICLE G3247

MATERIAL

Upper MESH/PU type fabric
 Lining MESH laminated breathable fabric
 Sole phylon/rubber, glued technology
 Toe cap composite 459
 Plate kevlar
 Insole ANATOMIC FOAM anatomically shaped EVA foam, supports longitudinal and transverse arches, absorbs shocks in the heel area

SIZE

36-46

UNIT

pair

PACKAGE

Units in a carton

10 pairs

Units in a box

1 pair

DIMENSIONS

Carton H x W x D (cm)

	36-42	43-46
Carton H x W x D (cm)	32.5 x 39.5 x 58	36.5 x 41.5 x 63
Carton (cbm)	0,0745	0,095

Carton (cbm)

0,0745

0,095

Size EUR

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	239	245	251	257	263	269	275	281	287	293	299	-	-	-	-	-
Foot length cm	-	23,4	24,0	24,6	25,2	25,8	26,4	27,0	27,6	28,2	28,8	29,4	-	-	-	-	-

Insole length mm

Foot length cm

DESCRIPTION

Safety shoes with a sporty design with a breathable fabric upper, polyurethane is used to strengthen the upper and the toe cover. The footwear is equipped with an anatomically shaped insole, made of a material that effectively dampens the tread and ensures comfort even when worn for a long time. The shoes have a composite toe and a flexible Kevlar insole against punctures. The sole made of a combination of phylon / rubber material ensures a soft tread and at the same time provides the highest level of anti-slip properties.

TECHNICAL SHEET



ARDON[®]
WORKWEAR
 & **OUTDOOR**

NORMS

(EU) 2016/425

EN ISO 20345:2022 Personal protective equipment – Safety footwear

Category S1PS FO SR

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water		
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heat up to 300 °C		
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts	✓	
-		
-		
-		

TECHNICAL SHEET



ARDON®

**WORKWEAR
& OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3247/36	8592390095831	10.00	1.000
G3247/37	8592390095848	11.50	1.150
G3247/38	8592390095855	12.00	1.200
G3247/39	8592390095862	12.50	1.250
G3247/40	8592390095879	13.00	1.300
G3247/41	8592390095886	13.50	1.350
G3247/42	8592390095893	14.00	1.400
G3247/43	8592390095909	15.50	1.550
G3247/44	8592390095916	16.00	1.600
G3247/45	8592390095923	16.50	1.650
G3247/46	8592390095930	17.00	1.700





ARDON®
WORKWEAR
& OUTDOOR





ARDON®

**WORKWEAR
& OUTDOOR**



TECHNICAL SHEET