



ARDON®
WORKWEAR
& OUTDOOR

ARDON® VOG S1

SAFETY SHOES



DRY AIR



WASH-FRIENDLY



ZIPPERS

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

ARDON® VOG S1

SAFETY SHOES

ARTICLE G1267

MATERIAL

Upper MICROFIBER with a thickness of 1,6 mm
 Lining MESH laminated breathable fabric
 Sole PU/PU, two-component spray coating, oil resistant, anti-static, antislip
 Toe cap steel 459
 Plate -
 Insole BASIC

SIZE 36-48

UNIT pair

PACKAGE

Units in a carton 10 pairs
 Units in a box 1 pair

DIMENSIONS

| | 36-42 | 43-48 | |
|-----------------------|------------------|--------------------|--|
| Carton H x W x D (cm) | 61 x 33,5 x 40,5 | 64,5 x 35,5 x 42,5 | |
| Carton (cbm) | 0,0828 | 0,0973 | |

| Size EUR | 35 | 36 | 37 | 38 | 39 | 40 | 41 | 42 | 43 | 44 | 45 | 46 | 47 | 48 | 49 | 50 | 51 |
|------------------|----|------|------|------|------|------|------|------|------|------|------|------|------|------|----|----|----|
| Insole length mm | - | 234 | 241 | 247 | 254 | 261 | 267 | 274 | 281 | 287 | 294 | 301 | 307 | 314 | - | - | - |
| Foot length cm | - | 22,9 | 23,6 | 24,2 | 24,9 | 25,6 | 26,2 | 26,9 | 27,6 | 28,2 | 28,9 | 29,6 | 30,2 | 30,9 | - | - | - |

DESCRIPTION

White safety sandal with microfiber upper and steel toe cap. Two-component polyurethane sole with the highest level of anti-slip protection.

TECHNICAL SHEET



ARDON[®]
WORKWEAR
 & **OUTDOOR**

NORMS

(EU) 2016/425

EN ISO 20345:2011

Personal protective equipment - Occupational footwear

Category

S1 SRC

| Categories | EN ISO 20345 | |
|--|--------------|--|
| E - energy absorption in the heel area | ✓ | |
| FO - resistance to oils and fuels | ✓ | |
| A - antistatic footwear | ✓ | |
| SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin | ✓ | |
| WR - upper resistant to water | | |
| Safety toe cap for toe protection | ✓ | |
| P - resistance to punctures (protective insole) | | |
| SRA - slip resistance ceramic floor tiles with SLS | | |
| HRO - resistance to contact heatup to 300 °C | | |
| HI-insulation of the bottom of the shoe against heat | | |
| CI-insulation of the bottom of the shoe against the cold | | |
| Splatters of molten metal | | |
| ESD – shoe protects against electrostatic discharge and can be used on EPA premises | | |
| The shoes do not contain metal parts | | |
| - | | |
| - | | |
| - | | |

TECHNICAL SHEET





ARDON®
WORKWEAR
& OUTDOOR

| CODE | EAN | CARTON WEIGHT (KG) | UNIT WEIGHT (KG) |
|-------------|---------------|-------------------------------|-----------------------------|
| G1267/36 | 8592390061102 | 10.3 | 1.03 |
| G1267/37 | 8592390061119 | 10.4 | 1.04 |
| G1267/38 | 8592390061126 | 10.6 | 1.06 |
| G1267/39 | 8592390061133 | 10.9 | 1.09 |
| G1267/40 | 8592390061140 | 11.1 | 1.11 |
| G1267/41 | 8592390061157 | 11.3 | 1.13 |
| G1267/42 | 8592390061164 | 11.5 | 1.15 |
| G1267/43 | 8592390061171 | 11.9 | 1.19 |
| G1267/44 | 8592390061188 | 12.5 | 1.25 |
| G1267/45 | 8592390061195 | 12.8 | 1.28 |
| G1267/46 | 8592390061201 | 13.2 | 1.32 |
| G1267/47 | 8592390061218 | 13.7 | 1.37 |
| G1267/48 | 8592390061225 | 14.2 | 1.42 |





ARDON®
WORKWEAR
& OUTDOOR





ARDON[®]
WORKWEAR
& OUTDOOR



TECHNICAL SHEET