



ARDON[®]
WORKWEAR
& **OUTDOOR**

ARDON[®] FORE S1P

SAFETY SHOES



DRY AIR



**DEFUSE
CONTROL**



REFLECTIVE

TECHNICAL SHEET



ARDON[®]
WORKWEAR
& OUTDOOR

ARDON[®] FORE S1P

SAFETY SHOES

ARTICLE G3196

MATERIAL

Upper ACTION NUBUK – cowhide leather with polyurethane / fabric coating
 Lining MESH laminated breathable fabric
 Sole PU/rubber, two-component spray coating, oil resistant, anti-static, antislip, resistant up to 300 °C
 Toe cap composite 604
 Plate kevlar
 Insole ANATOMIC FOAM anatomically shaped EVA foam, supports longitudinal and transverse arches, absorbs shocks in the heel area

SIZE

UNIT

PACKAGE

Units in a carton 10 pairs
 Units in a box 1 pair

DIMENSIONS

	36-39	40-43	44-48
Carton H x W x D (cm)	31.5 x 45.5 x 61.5	33.5 x 47.5 x 61.5	37 x 49.5 x 64
Carton (cbm)	0,0881	0,0979	0,117

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	237	243	250	257	263	270	277	283	290	297	303	310	317	-	-	-
Foot length cm	-	22,7	23,3	24,0	24,7	25,3	26,0	26,7	27,3	28,0	28,7	29,3	30,0	30,7	-	-	-

DESCRIPTION

Safety ankle shoes with upper made of ACTIONNUBUK material - cowhide leather with polyurethane coating. The wide PU / rubber sole has SRC anti-slip properties and is resistant to contact heat up to 300 ° C. The ANATOMIC FOAM insole ensures increased comfort of the shoes. The shoes are equipped with a composite toe and a flexible Kevlar insole against punctures.

TECHNICAL SHEET



ARDON[®]
WORKWEAR
 & **OUTDOOR**

NORMS

(EU) 2016/425

EN ISO 20345:2011 Personal protective equipment – Safety footwear

Category S1P HRO SRC

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water		
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heat up to 300 °C	✓	
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts		
-		
-		
-		

TECHNICAL SHEET





ARDON®

**WORKWEAR
& OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3196/36	8592390074652	13.90	1.390
G3196/37	8592390074669	14.20	1.420
G3196/38	8592390074676	14.60	1.460
G3196/39	8592390074683	15.20	1.520
G3196/40	8592390074690	15.40	1.540
G3196/41	8592390074706	16.10	1.610
G3196/42	8592390074713	16.70	1.670
G3196/43	8592390074720	17.20	1.720
G3196/44	8592390074737	17.80	1.780
G3196/45	8592390074744	18.30	1.830
G3196/46	8592390074751	18.80	1.880
G3196/47	8592390074768	19.20	1.920
G3196/48	8592390074775	19.50	1.950





ARDON®
WORKWEAR
& OUTDOOR





ARDON®

**WORKWEAR
& OUTDOOR**



TECHNICAL SHEET